

STANDARD OF DEPTH OF CUT EXTERNAL (RADIAL INFEED)

ISO Metric

Pitch (mm)	Total Cutting Depth	Number of Passes													Insert Type	
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	G-class ground inserts
0.5	0.31	0.10	0.08	0.07	0.06										MMT16ER050ISO	—
0.75	0.46	0.16	0.14	0.10	0.06										MMT16ER075ISO	—
1.0	0.61	0.18	0.15	0.12	0.10	0.06									MMT16ER100ISO	MMT16ER100ISO-S
1.25	0.77	0.19	0.17	0.14	0.11	0.10	0.06								MMT16ER125ISO	MMT16ER125ISO-S
1.5	0.92	0.22	0.21	0.17	0.14	0.12	0.06								MMT16ER150ISO	MMT16ER150ISO-S
1.75	1.07	0.22	0.21	0.16	0.13	0.11	0.09	0.09	0.06						MMT16ER175ISO	MMT16ER175ISO-S
2.0	1.23	0.24	0.23	0.17	0.16	0.14	0.12	0.11	0.06						MMT16ER200ISO	MMT16ER200ISO-S
2.5	1.53	0.26	0.23	0.19	0.17	0.15	0.13	0.12	0.11	0.11	0.06				MMT16ER250ISO	MMT16ER250ISO-S
3.0	1.84	0.27	0.25	0.20	0.18	0.16	0.14	0.13	0.12	0.12	0.11	0.10	0.06		MMT16ER300ISO	MMT16ER300ISO-S
3.5	2.15	0.33	0.30	0.24	0.21	0.18	0.17	0.15	0.14	0.14	0.13	0.12	0.12	0.06	MMT22ER350ISO	—
4.0	2.45	0.34	0.31	0.24	0.22	0.19	0.17	0.16	0.14	0.14	0.13	0.12	0.12	0.11	MMT22ER400ISO	—
4.5	2.76	0.38	0.34	0.28	0.24	0.22	0.20	0.18	0.16	0.16	0.15	0.14	0.13	0.12	MMT22ER450ISO	—
5.0	3.07	0.42	0.38	0.32	0.27	0.24	0.22	0.20	0.18	0.18	0.17	0.16	0.15	0.12	MMT22ER500ISO	—

American UN

Pitch (thread/inch)	Total Cutting Depth	Number of Passes													Insert Type		
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	G-class ground inserts	M-class inserts with 3-D chip breakers
32	0.49	0.17	0.15	0.11	0.06										MMT16ER320UN	—	
28	0.56	0.17	0.14	0.10	0.09	0.06									MMT16ER280UN	—	
24	0.65	0.18	0.16	0.14	0.11	0.06									MMT16ER240UN	—	
20	0.78	0.20	0.18	0.13	0.11	0.10	0.06								MMT16ER200UN	—	
18	0.87	0.22	0.20	0.15	0.13	0.11	0.06								MMT16ER180UN	—	
16	0.97	0.22	0.20	0.15	0.12	0.11	0.11	0.06							MMT16ER160UN	MMT16ER160UN-S	
14	1.11	0.23	0.21	0.16	0.13	0.11	0.11	0.10	0.06						MMT16ER140UN	MMT16ER140UN-S	
13	1.20	0.25	0.22	0.17	0.14	0.13	0.12	0.11	0.06						MMT16ER130UN	—	
12	1.30	0.28	0.23	0.18	0.16	0.14	0.13	0.12	0.06						MMT16ER120UN	MMT16ER120UN-S	
11	1.42	0.28	0.23	0.19	0.16	0.14	0.13	0.12	0.11	0.06					MMT16ER110UN	—	
10	1.56	0.28	0.24	0.19	0.16	0.14	0.13	0.13	0.12	0.11	0.06				MMT16ER100UN	—	
9	1.73	0.34	0.29	0.22	0.17	0.15	0.14	0.13	0.12	0.11	0.06				MMT16ER090UN	—	
8	1.95	0.35	0.30	0.24	0.19	0.16	0.15	0.14	0.13	0.12	0.11	0.06			MMT16ER080UN	—	
7	2.22	0.37	0.33	0.28	0.24	0.20	0.17	0.16	0.15	0.14	0.12	0.06			MMT22ER070UN	—	
6	2.60	0.42	0.35	0.29	0.25	0.21	0.18	0.17	0.16	0.15	0.13	0.12	0.11	0.06	MMT22ER060UN	—	
5	3.12	0.43	0.39	0.31	0.27	0.24	0.22	0.20	0.19	0.19	0.18	0.17	0.15	0.12	0.06	MMT22ER050UN	—

Whitworth for BSW, BSP

Pitch (thread/inch)	Total Cutting Depth	Number of Passes													Insert Type		
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	G-class ground inserts	M-class inserts with 3-D chip breakers
28	0.58	0.17	0.14	0.11	0.10	0.06									MMT16ER280W	—	
26	0.63	0.18	0.15	0.13	0.11	0.06									MMT16ER260W	—	
20	0.81	0.20	0.18	0.14	0.12	0.11	0.06								MMT16ER200W	—	
19	0.86	0.21	0.19	0.15	0.13	0.12	0.06								MMT16ER190W	MMT16ER190W-S	
18	0.90	0.25	0.19	0.15	0.13	0.12	0.06								MMT16ER180W	—	
16	1.02	0.21	0.18	0.15	0.13	0.11	0.09	0.09	0.06						MMT16ER160W	—	
14	1.16	0.23	0.21	0.17	0.14	0.12	0.12	0.11	0.06						MMT16ER140W	MMT16ER140W-S	
12	1.36	0.27	0.25	0.20	0.16	0.15	0.14	0.13	0.06						MMT16ER120W	—	
11	1.48	0.27	0.24	0.20	0.17	0.15	0.14	0.13	0.12	0.06					MMT16ER110W	MMT16ER110W-S	
10	1.63	0.27	0.25	0.20	0.17	0.15	0.15	0.13	0.13	0.12	0.06				MMT16ER100W	—	
9	1.81	0.28	0.26	0.21	0.18	0.16	0.15	0.14	0.13	0.12	0.12	0.06			MMT16ER090W	—	
8	2.03	0.30	0.27	0.22	0.19	0.17	0.16	0.15	0.14	0.13	0.12	0.12	0.06		MMT16ER080W	—	
7	2.32	0.34	0.32	0.26	0.22	0.20	0.18	0.17	0.16	0.15	0.14	0.12	0.06		MMT22ER070W	—	
6	2.71	0.35	0.33	0.27	0.23	0.21	0.20	0.19	0.17	0.16	0.15	0.14	0.13	0.12	0.06	MMT22ER060W	—
5	3.25	0.42	0.40	0.35	0.29	0.26	0.24	0.22	0.20	0.19	0.18	0.17	0.15	0.12	0.06	MMT22ER050W	—

BSPT

Pitch (thread/inch)	Total Cutting Depth	Number of Passes													Insert Type	
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	G-class ground inserts
28	0.58	0.17	0.14	0.11	0.10	0.06									MMT16ER280BSPT	—
19	0.86	0.22	0.19	0.15	0.12	0.12	0.06								MMT16ER190BSPT	MMT16ER190BSPT-S
14	1.16	0.24	0.20	0.17	0.14	0.12	0.12	0.11	0.06						MMT16ER140BSPT	MMT16ER140BSPT-S
11	1.48	0.25	0.23	0.21	0.18	0.16	0.14	0.13	0.12	0.06					MMT16ER110BSPT	MMT16ER110BSPT-S

(Note) • Set the finishing allowance on a diameter at approx. 0.1mm when using a full form insert.

• Please note the cutting depth and the number of passes when a corner radius of a partial form insert or of an internal threading insert is small to prevent damage to the insert corner.

• Please set the cutting depth sufficiently deep enough on materials such as hardened steel or austenitic stainless steel to help prevent premature wear and chipping caused by the outer layer of the material.

STANDARD OF DEPTH OF CUT EXTERNAL (RADIAL INFEED)

Round DIN 405

Pitch (thread/ inch)	Total Cutting Depth	Number of Passes														Insert Type
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	
10	1.27	0.23	0.21	0.20	0.19	0.16	0.12	0.10	0.06							MMT16ER100RD
8	1.59	0.23	0.21	0.20	0.19	0.18	0.16	0.14	0.12	0.10	0.06					MMT16ER080RD
6	2.12	0.26	0.25	0.24	0.22	0.21	0.19	0.17	0.16	0.14	0.12	0.10	0.06			MMT16ER060RD
4	3.18	0.34	0.33	0.32	0.30	0.28	0.26	0.24	0.22	0.20	0.19	0.17	0.15	0.12	0.06	MMT22ER040RD

ISO Trapezoidal 30°

Pitch (mm)	Total Cutting Depth	Number of Passes														Insert Type
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	
1.5	0.90	0.23	0.21	0.16	0.13	0.11	0.06									MMT16ER150TR
2.0	1.25	0.29	0.26	0.21	0.17	0.14	0.12	0.06								MMT16ER200TR
3.0	1.75	0.32	0.31	0.24	0.19	0.18	0.17	0.15	0.13	0.06						MMT16ER300TR
4.0	2.25	0.33	0.32	0.24	0.22	0.21	0.17	0.16	0.15	0.14	0.13	0.12	0.06			MMT22ER400TR
5.0	2.75	0.35	0.32	0.26	0.24	0.22	0.21	0.19	0.19	0.17	0.15	0.14	0.13	0.12	0.06	MMT22ER500TR

American ACME

Pitch (thread/ inch)	Total Cutting Depth	Number of Passes														Insert Type
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	
12	1.19	0.27	0.23	0.20	0.17	0.14	0.12	0.06								MMT16ER120ACME
10	1.52	0.29	0.25	0.21	0.18	0.16	0.14	0.12	0.11	0.06						MMT16ER100ACME
8	1.84	0.30	0.26	0.22	0.19	0.16	0.15	0.14	0.13	0.12	0.11	0.06				MMT16ER080ACME
6	2.37	0.34	0.30	0.27	0.24	0.21	0.19	0.16	0.14	0.12	0.12	0.11	0.11	0.06		MMT22ER060ACME
5	2.79	0.36	0.33	0.30	0.26	0.23	0.20	0.18	0.17	0.16	0.15	0.14	0.13	0.12	0.06	MMT22ER050ACME

UNJ

Pitch (thread/ inch)	Total Cutting Depth	Number of Passes														Insert Type
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	
32	0.46	0.16	0.14	0.10	0.06											MMT16ER320UNJ
28	0.52	0.16	0.12	0.09	0.09	0.06										MMT16ER280UNJ
24	0.61	0.17	0.14	0.14	0.10	0.06										MMT16ER240UNJ
20	0.73	0.19	0.16	0.13	0.10	0.09	0.06									MMT16ER200UNJ
18	0.81	0.23	0.18	0.14	0.10	0.10	0.06									MMT16ER180UNJ
16	0.92	0.26	0.21	0.14	0.12	0.10	0.09									MMT16ER160UNJ
14	1.05	0.26	0.23	0.17	0.12	0.11	0.10	0.06								MMT16ER140UNJ
12	1.22	0.28	0.27	0.20	0.17	0.13	0.11	0.06								MMT16ER120UNJ
10	1.47	0.30	0.29	0.21	0.15	0.13	0.12	0.11	0.10	0.06						MMT16ER100UNJ
8	1.83	0.31	0.30	0.23	0.18	0.15	0.14	0.13	0.12	0.11	0.10	0.06				MMT16ER080UNJ

API Buttress Casing

Pitch (thread/ inch)	Total Cutting Depth	Number of Passes														Insert Type
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	
5	1.55	0.25	0.23	0.17	0.15	0.13	0.12	0.12	0.11	0.11	0.10	0.06				MMT22ER050APBU

API Round Casing&Tubing

Pitch (thread/ inch)	Total Cutting Depth	Number of Passes														Insert Type
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	
10	1.41	0.25	0.23	0.16	0.14	0.12	0.12	0.12	0.11	0.10	0.06					MMT16ER100APRD
8	1.81	0.25	0.24	0.19	0.16	0.14	0.14	0.13	0.13	0.13	0.13	0.11	0.06			MMT16ER080APRD

American NPT

Pitch (thread/ inch)	Total Cutting Depth	Number of Passes														Insert Type
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	
27	0.66	0.15	0.13	0.12	0.11	0.09	0.08	0.06								MMT16ER270NPT
18	1.01	0.20	0.16	0.14	0.13	0.12	0.11	0.09	0.06							MMT16ER180NPT
14	1.33	0.23	0.19	0.16	0.14	0.13	0.12	0.11	0.10	0.09	0.06					MMT16ER140NPT
11.5	1.64	0.24	0.19	0.17	0.15	0.15	0.13	0.13	0.12	0.11	0.10	0.09	0.06			MMT16ER115NPT
8	2.42	0.33	0.28	0.23	0.20	0.18	0.16	0.15	0.14	0.13	0.12	0.12	0.11	0.10	0.06	MMT16ER080NPT

(Note) • Set the finishing allowance on a diameter at approx. 0.1mm when using a full form insert.

• Please note the cutting depth and the number of passes when a corner radius of a partial form insert or of an internal threading insert is small to prevent damage to the insert corner.

• Please set the cutting depth sufficiently deep enough on materials such as hardened steel or austenitic stainless steel to help prevent premature wear and chipping caused by the outer layer of the material.